

Instant Voltage Testers

Volt Stick[®]
Instant Voltage Tester



The original and still the best, **Volt Stick** is an instant tester for safely checking the presence of an AC voltage, without making any disconnections in cables, wall sockets, fuses, circuit breakers, junction boxes, etc. No current flow is needed for correct operation.

The red indicator in the tip will illuminate on detection of AC voltage simply by applying the tip close to any connection point, or moving it along any insulated cable.

The range includes the standard and intrinsically-safe ATEX versions for use in hazardous areas such as chemical plants, oil refineries and off shore rigs.

Features:

- Locates breaks in cables
- Detects blown fuses inside plugs or fuse holders
- Distinguishes between live and neutral wires in both single and three-phase supplies
- Identifies voltage-carrying cables in junction boxes
- Identifies faulty in-line switches
- Locates defective in-series light bulbs

All **Volt Stick** models are fully approved to IEC 61010-1, CAT III 1000V AC and CE. **Are yours?!!**



Specifications:

Model:	Volt Stick Yellow	Voltstick BP Black	Voltstick LV50	Voltstick EXP 240
Voltage Range:	220 ~ 230 Volts AC	220 ~ 230 Volts AC	50~1000V for IN02470	220 ~ 230 Volts AC
Sensitivity:	Indicator will illuminate at 4mm distance of a 2.5mm{+2} conductor carrying 220V	Indicator will illuminate at 4mm distance of a 2.5mm{+2} conductor carrying 220V	Indicator will illuminate at 4mm distance of a 2.5mm{+2} conductor carrying 50V	Indicator will illuminate at 4mm distance of a 2.5mm{+2} conductor carrying 220V
Response Time:	Immediate	Immediate	Immediate	Immediate
Intrinsically Safe:	No	No	Yes	Yes
Power Requirements:	2 x Standard AAA alkaline batteries (supplied)	2 x Standard AAA alkaline batteries (supplied)	2 x Standard AAA alkaline batteries (supplied)	2 x Standard AAA alkaline batteries (supplied)
RH:	80% @ 30°C, 50% @ 40°C	80% @ 30°C, 50% @ 40°C	80% @ 30°C, 50% @ 40°C	80% @ 30°C, 50% @ 40°C
Operating Temp:	-20 ~ +50° C	-20 ~ +50° C	-20 ~ +50° C	-20 ~ +50° C
Overvoltage:	CAT III 1000V AC	CAT III 1000V AC	CAT III 1000V AC	CAT III 1000V AC
Dimensions:	145(L) x 18(W) x 20(H) mm	145(L) x 18(W) x 20(H) mm	145(L) x 18(W) x 20(H) mm	145(L) x 18(W) x 20(H) mm
Weight:	35g (inc. batteries)	35g (inc. batteries)	35g (inc. batteries)	35g (inc. batteries)